



INTONACATRICI

Since 1986, Edilmac builds and repairs plastering machine, plaster power float, jointing / filling machine, transporters and mixers for traditional mortar, pre-mixed plaster, finish and special restructuring plaster.

Via Bacchiglione n° 2 - 35030 Cervarese Santa Croce - Padova – ITALY - Phone: +39 049 9915268
Internet : <https://www.edilmac.net/en/>

Single-phase!



CK 20

CK 20 - Single-phase plastering machine for ready-mix dry mortar.

CK 20 plastering machine is a Single-phase worm vertical mixing pump, ideal to mix, transport and spray all kinds of ready-mix dry mortars with max. aggregate size up to 3 mm, cement, lime or gypsum based, for indoor, outdoor and ceilings, self-levelling floor screed and special fibered mortars.

CK 20 plastering machine ensuring excellent versatility, electronic range variation of pump output is perfect to do any type of plastering, from small to medium buildings.

CK 20 can be carrying everywhere by its small size and weight and it can be disassemble in 3 parts for easy manual carrying to the floors, therefore ideal for small buildings reconstruction in a urban or historical town area because, in fact it can be connected to classic home buildings 230 V single-phase 3 kw power supply, without compromised and ensuring always excellent performance.

FEATURES

- It mixes perfectly the material and it allows to adjust the mixture density with the dosing valve.
- The machine is handy and provided with wheels (2 with brake) and hooks for hanging, it can be disassemble in 3 parts (see the below figure).
- It is easy to use
- It is provided with electronic inverter for maximum performance and lower power consumption.
- The plaster machine is ergonomic and strong.
- It is provided with water pump.
- The new type of mixing chamber mixes without problems every kinds of ready-mix plasters for indoor and outdoor.
- It is soundless in the working pause too
- It needs little maintenance and it can be cleaned quickly

TECHNICAL SPECIFICATION

Power consumption - 3 Kw - 230 V single-phase

Pumping distance - up to 20 m

Pumping height - up to 8 m

Pump output capacity - adjustable from 5 to 20 l/min.

Plaster pump motor 2,2 Kw

Air compressor 0,5 Kw

Dosing pump motor 0.3 Kw

STANDARD EQUIPMENT

Mortar hose 10 m

Air hose 10 m

Spraying gun with nozzles Ø 13

Instructions manual, toolbox, accessories and declaration of conformity

SIZE

Length- 1100 mm

Width - 600 mm

Loading height - 930 mm

Max height - 1400 mm

Hopper capacity - 90 l

Total Weight - 210 kg



CK 20 disassembled in 3 parts, easy to carry.



www.edilmac.net/en/ck20/

Reseller / Area Agent