

EDILMAC

INTONACATRICI

Since 1986, Edilmac builds and repairs plastering machine, plaster power float, jointing / filling machine, transporters and mixers for traditional mortar, pre-mixed plaster, finish and special restructuring plaster.

Via Bacchiglione n° 2 - 35030 Cervarese Santa Croce - Padova – ITALY - Phone: +39 049 9915268
Internet : <https://www.edilmac.net/en/>

Three-phase



Evutech

**EVUTECH - Pistons plastering machine
three-phase for traditional mortar.**

Evutech - 400 V Three-phase, is a plastering and transport machine for traditional mortars and premixed wet mortars especially for restructuring, based on new Edilmac piston pump concept "side to side" which have a particular axial execution, that expands the range of suitable mortars and ensures an excellent uniformity of sprayed material.

The plastering machine **Evutech** has high performance and high hopper capacity, so it's suitable for medium and large buildings company, it guarantees excellent performances for spraying and transport traditional mortar based on cement, lime, and any type of sand, on indoor and outdoor walls and ceilings, premixed wet mortars, fine concrete (up to 12 mm) spritz beton on panels and metallic net, jet of slab, It's possible to spray anti-retirement or expansive mortars, for consolidation of damaged or degraded structures of civil and industrial buildings, jet of micropiles, transport of masonry mortars, execution of first spraying liquid mortar, ecological and thixotropic plasters, mortars for restorations of buildings and flats.

Evutech is distinguished for excellent reliability and high performance level, then it can be perfectly used with the most difficult work conditions, continuously for many hours.

FEATURES

- ✓ New Edilmac concept of axial pistons pump "side to side" that expands the range of used plasters and ensures an excellent uniformity of sprayed material.
- ✓ Air compressor provided on standard equipment
- ✓ Electric vibrating screen on standard equipment.
- ✓ Pneumatic remote control on the spray gun
- ✓ Anti-clogging safety system against high pressures on standard equipment..
- ✓ Robust and manageable, is equipped with pneumatic tubeless wheels, handles for moving and hooks for lifting
- ✓ It can be used with **continuous mixers like Edilmac L 25 or L 60** and any type of concrete mixers.
- ✓ Fast cleaning and low maintenance.
- ✓ High durability of piston pump, more than 30.000 m² of mortars sprayed before maintenance.

TECHNICAL SPECIFICATIONS

Power consumption – 6,8 Kw - 400 V three-phase

Motor pump 4 Kw.

Air compressor 1,8 Kw

Hopper agitator motor 0,75 Kw.

Electric vibrating screen 0,25 Kw.

Max pumping distance – up to 150 m.

Max pumping height – up to 40 m.

Pump output capacity – up to 55 l/min.

Max. pressure pump - 20 bar.

Aggregate size – up to 12 mm

STANDARD EQUIPMENT

Mortar hose Ø 50 - 20 m.

Mortar hose Ø 40 - 10 m.

Air hose Ø 10x17 - 31 m.

Spraying Gun, instructions manual, toolbox, accessories and declaration of conformity .

SIZE

Length - 2000 mm.

Width - 1400 mm.

Max. Height - 1000 mm.

Load Height - 750 mm.

Hopper capacity - 250 l.

Total



INTONACATRICI

Reseller / Area Agent

www.edilmac.net/en/evutech/